

EZ-GLO



EZGLO IS A HIGH GLOSS, NON-YELLOWING ACRYLIC FLOOR POLISH FOR USE ON ALL TYPES OF SEALED FLOORS. IT NOT ONLY DRIES TO A HIGH GLOSS FINISH, IT CAN BE MAINTAINED BY SPRAY BUFFING.

ENVIRONMENTAL IMPACT:

EZGlo contains no toxic heavy metals or butyl solvents and has very low **VOC's**.

APPLICATIONS:

EZGlo is used to maintain floors in a brilliant polished condition with minimum of labor. All types of sealed concrete floors as well as sealed wood and composition floors will improve their appearance and decrease maintenance costs with the use of **EZGlo**.

BENEFITS:

- **EZGlo** produces a beautiful high gloss, wet look shine on drying, without buffing.
- Buffs up to a super shine using simple Spray Buffing techniques with a mixture of one part of **EZGlo** and 3 parts water. No special equipment is required and re-coating is reduced to a minimum.
- Highly detergent resistant. **EZGlo** is not harmed by repeated scrubbing with a neutral detergent, or damp mopping between buffings.
- Restore worn areas by re-coating with **EZGlo**. Just damp mop, apply and let dry. Spray Buffing will blend in the re-coated area.
- **EZGlo** is highly slip resistant and meets the **ASTM D-2407** requirement for slip resistance
- **EZGlo** is economical. One gallon covers over 1200 sq. ft. per coat, and lasts for months without re-coating. Simple Spray Buffing maintenance keeps the clean, bright polished look for months, and the acrylic polymers do not ever yellow.

HOW TO USE:

- Remove old polish thoroughly by scrubbing with **CitraPro**. Rinse floor well and let dry completely. Spread **EZGlo** in a thin even coat over the floor using a Lambs wool Applicator or a clean yarn mop. Allow to dry completely, about 25 to 30 minutes. Apply a second coat and let dry completely before allowing traffic on the floor.
- **Spray Buffing:** Dilute 1 part of **EZGlo** with 3 parts of water. Using a Trig Mist sprayer, mist lightly over a 1 sq. meter (10 sq. ft.) area and buff with a polishing pad until all liquid disappears and a brilliant shine appears. Repeat this until the entire floor is renovated and polished
- **Maintenance:** Occasional damp mopping with a neutral detergent will maintain the smooth glossy surface. In Heavy Traffic areas, after mopping and rinsing, let dry and apply a thin coat of **EZGlo**.

PROPERTIES:

Type: Super acrylic floor polish
Color: Colorless, non_yellowing
Odor: Very mild
Toxicity: Non-toxic
Flammability: Non-Flammable
pH: 8.5-8.9
Composition: Acrylic polymer emulsion, ethylene copolymers, proprietary additives and quality control agents.

