

SDI STAMP SEAL XTRA GLOSS

XTRA GLOSS, NON-YELLOWING ULTRA HIGH GLOSS LACQUER

VOC COMPLIANT SEALERS

XTRA GLOSS

PRODUCT DESCRIPTION

XTRA GLOSS is an ultra high gloss, non-yellowing, pure acrylic concrete lacquer style sealer designed for decorative concrete. **XTRA GLOSS** offers improved resistance to rain, the sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. Applying **XTRA GLOSS** to exposed aggregate will also help to eliminate loose pebbles and premature wear. **XTRA GLOSS** offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. **XTRA GLOSS** can be considered an ultimate multi-use concrete sealer.

BENEFITS/FEATURES

- ◆ Can be used as a means of dustproofing most concrete surfaces.
- ◆ Due to our 100% pure acrylic formula, this product will not yellow under ultraviolet exposure.
- ◆ Fast drying time highly reduces the risk of trapped solvent or other types of moisture issues.
- ◆ Low 400 VOC content allows for broader range of use across the country.

RECOMMENDED APPLICATIONS

XTRA GLOSS is recommended for use on Stamped Concrete, Stenciled Concrete, Acid Stained Concrete, Overlaid Concrete, Exposed Aggregate Concrete, Broom Finish Concrete, and Trowel Finish Concrete. Other uses may be acceptable.

TECHNICAL INFORMATION

Solids.....	30%	Wet Appearance.....	Clear to lightly cloudy
Drying Time.....	30 min. - 1 hour	Dry Appearance.....	Clear and Ultra High Gloss
Re-Coat Time.....	4 - 24 hours	VOC Content.....	<400 g/l
Foot Traffic.....	4 - 6 hours	Blush Resistance.....	Good
Wheel Traffic.....	24 - 48 hours	Solvent Resistance.....	Minimal
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	Excellent

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

This product is VOC and OTC compliant in all states where compliance is 400 VOC's or less.

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First</u>	<u>Optional Second Coat</u>
New (unsealed) concrete	200-300 ft ²	300-350 ft ²
Old (sealed) concrete	300-350 ft ²	300-350 ft ²

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

SHELF LIFE

XTRA GLOSS has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

XTRA GLOSS is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.



SEALANT DEPOT, INC.

1100 Taylor's Ln. Phone: (856) 829-7325

Cinnaminson, NJ 08077 Fax: (856) 829-0430

Visit us online at: www.sealantdepot.com