

SDI STAMP SEAL PENETRATING

NON-YELLOWING, PENETRATING, ACRYLIC CONCRETE SEALER

PRODUCT DESCRIPTION

PENETRATING is a non-yellowing, pure acrylic concrete sealer designed for all types of concrete. **PENETRATING** offers improved resistance to rain, the sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. Applying **PENETRATING** to exposed aggregate will also help to eliminate loose pebbles and pre-mature wear. **PENETRATING** offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. **PENETRATING** can be considered an ultimate multi-use concrete sealer.

BENEFITS/FEATURES

- ◆ Can be used as a means of dustproofing most concrete surfaces.
- ◆ Due to our 100% pure acrylic formula, this product will not yellow under ultraviolet exposure.
- ◆ Deep penetrating and ultra low viscosity formula allows for easy application through sprayers
- ◆ It's ease of use and it's medium gloss appearance makes this product a customer favorite.
- ◆ Low 400 VOC content allows for broader range of use across the country.

RECOMMENDED APPLICATIONS

2000 Supreme is recommended for use on Stamped Concrete, Stenciled Concrete, Acid Stained Concrete, Overlaid Concrete, Exposed Aggregate Concrete, Broom Finish Concrete, and Trowel Finish Concrete. Other uses may be acceptable.

TECHNICAL INFORMATION

Solids.....	25%	Wet Appearance.....	Clear to lightly cloudy
Drying Time.....	1 - 2 hours	Dry Appearance.....	Clear and Medium Gloss
Re-Coat Time.....	4 - 24 hours	VOC Content.....	<400 g/l
Foot Traffic.....	4 - 6 hours	Blush Resistance.....	Good
Wheel Traffic.....	24 - 48 hours	Solvent Resistance.....	Minimal
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	Excellent

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

•• ASTM C 309, Type 1, Class A
•• ASTM C-1315 Type 1, Class A

•• ASTM C 309, Type 1, Class B
•• DRIED COATING IS USDA ACCEPTED

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First</u>	<u>Optional Second Coat</u>
New (unsealed) concrete	250-350 ft ²	350-400 ft ²
Old (sealed) concrete	350-400 ft ²	350-400 ft ²

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

SHELF LIFE

PENETRATING has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

PENETRATING is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.



SEALANT DEPOT, INC.

1100 Taylor's Ln. Phone: (856) 829-7325
Cinnaminson, NJ 08077 Fax: (856) 829-0430

Visit us online at: www.sealantdepot.com

VOC COMPLIANT SEALERS

PENETRATING